

XPR-7TR Two Post Turf Lifts



- o 7,000-pound lifting capacity
- o Single piece columns
- o Single point safety release
- o Dual hydraulic, "Direct-Drive" Cylinders
- o Electric / hydraulic power system
- o Large, 19" x 17" steel base plates
- o Self-lubricating dura-glide polyethylene bearing system

- o Safety locks in each column spaced every 3-inches
- o Fully adjustable full-width wheel pan and fork assemblies to accommodate a wide variety of vehicle wheelbases
- o Full-width wheel pan ideal for single or dual rear wheeled vehicles
- o heavy-duty dual 3/8" equalizer cable with oversize sheaves
- o Padded overhead safety-shutoff bar



BendPak's XPR-7TR turf lift is the most versatile lawn maintenance and utility vehicle lift on the market – all backed by a service and support excellence that only BendPak's 40-year experience can provide. The XPR-7TR turf lift greatly increases speed and maintenance repair work on all popular sizes of turf maintenance equipment ranging from large fairway mowers to greens mowers, utility carts, sand groomers, fertilizer sprayers, golf and refreshment carts. Fully adjustable full-width wheel pan and fork assemblies fit a wide array of wheel arrangement. The XPR-7TR provides open access to the gear box, blades, reels and other components for increased shop efficiency.

The XPR-7TR turf attachments can be easily removed to convert for regular automotive and light truck service work with the purchase of standard swing arm assemblies.

MODEL - XPR-7TR

| | |
|---|-----------------------|
| Lifting Capacity* | 7,000 Lbs. / 3175 Kg. |
| *Max Load / Wheel Pan: | 3,500 Lbs. / 1588 Kg. |
| *Max Load per Fork: | 1,750 Lbs. / 794 Kg. |
| Height Overall(*): | 145" / 3683 mm. |
| Width Overall (Outside of Base Plate): | 145" / 3683 mm. |
| Width (Outside of Columns): | 137" / 3480 mm. |
| Floor to Overhead Switch(*): | 141" / 3581 mm. |
| Inside Columns: | 115" / 2921 mm. |
| Rise: | 69" / 1753 mm. |
| Drive-Thru Clearance: | 106" / 2692 mm. |
| Motor (**): | 220 VAC / 60 Hz. 1Ph. |
| Time of full Rise: | 45 Seconds |

* An optional bolt-on top extension for columns raises the overhead bar an additional 24". Must be ordered from factory at time of order.

** Special voltages available upon request.

The design, material and specifications are subject to change without notice.



www.liftmaster.com

Liftmaster



GARAGE EQUIPMENT LIMITED

Tel: 01420 549038/ 549037

Fax: 01420 549036

E-mail: info@liftmaster.com